



**SCRATCH AND BROWN PREBLENDED STUCCO**

SPEC MIX® Scratch and Brown Preblended Stucco is a custom blend of cementitious materials, additives and aggregates meeting ASTM C 926 requirements and designed to be used as the scratch and/or brown coat in a traditional three-coat stucco system.



**SCRATCH AND BROWN PREBLENDED FIBER STUCCO**

SPEC MIX® Scratch and Brown Preblended Fiber Stucco is a custom blend of cementitious materials, additives, aggregates and alkali resistant fibers meeting ASTM C 926 requirements and designed as a durable and cost effective alternative to traditional three or two-coat stucco systems.



**FIBER BASE COAT (ICC CERTIFIED)**

SPEC MIX® FIBER BASE COAT is a high performance premixed stucco base coat for commercial and residential applications. Designed to minimize crazing and cracking, it can be used for all 3/4" - 7/8" (19 - 22.2 mm) and 3/8" - 1/2" (9.5 - 12.7 mm) thick stucco applications and is ideal for 1-coat and traditional scratch and brown stucco applications. When walls are assembled in accordance with SPEC MIX ESR Report number 1471, SPEC MIX FIBER BASE COAT can also be used for 1-hour fire resistive wall assemblies and for noncombustible construction.



**COLORED FINISH COAT PREBLENDED STUCCO**

SPEC MIX® Colored Finish Coat Preblended Stucco is a custom blend of cementitious materials, additives, aggregates and color pigment meeting ASTM C 926 requirements. It is designed as the finish coat for traditional two- or three-coat stucco systems.

Package Size	Spec Mix® Product	Nominal Thickness	Approximate Coverage*
80 lb. Bag	Scratch & Brown Preblended Stucco	3/4"	11 - 12 ft <sup>2</sup>
3000 lb. Bag	Scratch & Brown Preblended Stucco	3/4"	412—454 ft <sup>2</sup>
80 lb. Bag	Scratch & Brown Preblended Fiber Stucco	3/8"	23 - 25 ft <sup>2</sup>
3000 lb. Bag	Scratch & Brown Preblended Fiber Stucco	3/8"	862 - 937 ft <sup>2</sup>
80 lb. Bag	Colored Finished Coat Preblended Stucco	1/8"	66 - 71 ft <sup>2</sup>
3000 lb. Bag	Colored Finished Coat Preblended Stucco	1/8"	2475 - 2663 ft <sup>2</sup>

\*Typical Cementitious Finish Coats are 1/8" nominal thickness in one application

\*Typical S & B w/Fiber Systems are 3/8" nominal thickness in one application

\*Typical scratch and brown coats combined are 3/4" nominal thickness

\*Coverage may vary due to ambient temperature, surface temperature, surface porosity, mixing and/or application methods. Due to these uncontrollable factors, TCC assumes no liability in their accuracy or reliability.